

SIAMESE RG59 SOL BC 95% CCA BRD +18/2 BC STR CMR

Part Number: BC-RG59182BCSIAM



Listings

Listings c(ETL)us UL Standard 13 and UL 444, TIA/EIA-568-C.2 NEC Articles 800

Constructions

Conductor	20 AWG Solid CCS
Dielectric	Foamed PE
Nom. Dielectric Wall Thickness	0.057"
Nom. Dielectric Diameter	0.146"
Shield	95% CCA Braid
Nom. Shield Diameter	0.174"
Jacket Material	PVC
Jacket Thickness	0.034" nom.
Nom. Overall Cable Diameter	0.236" 0.493"
Approximate Calbe Weight (lbs./Kft.)	51 lbs
Flame Rating	UL1581 Vertical Tray Flame Test
Rip Cord	No

Electrical Properties

Nom. DC Resistance per Conductor @ 20°C	7.5Ohms/M' @20°C
Capacitance Between Conductors @ 1 KHz	16.3 F/Ft. nom.
Operating Voltage	
Temperature Rating	max 60° C
Min. Velocity of Propagation	78%
Frequency Rating	max 1000 MHz

Insulation Color	White
Jacket Color	Black
Legend (Surface Ink Print)	**/**FT comCables RG59SIAM RG59 20AWG SOL BC 95% CCA BRD + 18/2 CCA c(ETL)us 5000838 Type CL2 UV Protected DC 1014 ZONE 0 1 2 3 4 5 6 7 8 9 "For CCTV Only"